



PERSONAL
COMPUTERS



SMALL
COMPUTERS
NETWORK

iDialog / iDialog Plus

400-800 VA / 400-1600 VA

single-phase

iDialog / iDialog Plus 400-800 VA / 400-1600 VA




The **iDialog** UPS has been designed to protect PCs and critical peripherals in home and small office environments. iDialog is easy to install and provides powerful, economic protection for:

- IT equipment including PCs, Media Centers, PoE, VoIP and other such peripherals
- TVs, Home Cinemas, Satellite and Digital Terrestrial receivers, DVD readers and writers
- Modems and xDSL routers
- Small household appliances

CHARACTERISTICS

- Maximum power protection with **PowerShield³** UPS monitoring and shutdown software available for free download from our website www.riello-ups.com
- Suitable for installation on PC's running Windows Vista, 2003, XP, 2000, Me, 98; Linux, Mac OSX and the Sun Solaris operating system.
- Compact dimensions and ergonomic design: **iDialog** can be placed on a desk top or other convenient location, with easy to access connections and informative front panel.
- Front panel LCD display (**Plus** version only) providing status, load and battery information and LEDs (standard version).

Particolare dei display



battery information and LEDs (standard version).

- Silent running: **iDialog** can be used to protect other sensitive electronic devices including Home Cinemas, CD Writers, DVD players, Satellite and Digital Terrestrial receivers.

MODELS	ID 40	ID 60	ID 80	IDP 40	IDP 60	IDP 80	IDP 110	IDP 160
POWER	400VA/240W	600VA/360W	800VA/480W	400VA/240W	600VA/360W	800VA/480W	1100VA/660W	1600VA/960W
INPUT								
Rated voltage	220-240 Vac							
Voltage range	230 Vac (+20/-25%)							
Frequency	50/60 Hz auto sensing							
OUTPUT								
Voltage on mains operation	230 Vac (+/- 15%)							
Voltage on battery operation	230 Vac (+/- 10%)							
Frequency on battery operation	50 or 60 Hz (+/- 1%)							
BATTERIES								
Type	VRLA AGM Maintenance-free lead-acid							
Recharge time	6-8 h							
ENVIRONMENTAL								
Weight (kg)	3		3.2		3.4		6.6	7
Dimensions (hwd) (mm)	192 x 90 x 232						275 x 97x 315	
Tel/Modem protection	RJ11/45 connectors							
Communication	n.d.			USB				
Output sockets	4 IEC			4 IEC or 3 Schuko/Italian or 3 french			6 IEC or 4 Schuko/Italian or 4 french	
Safety compliance	EN 62040-1-1 and Directives 73/23 EC, 93/68 EC, EN 62040-3							
EMC conformance	EN 62040-2 and Directives 2004/108 EC, 93/68 EC							
Marks	CE							
Operating temperature	0°C / +40°C							
Colour	Dark grey							
Altitude and relative humidity	6000 meters max. elevation, < 95% non condensing							
Accessories provided	2 output supply cables (IEC version), 1 USB cable (plus version), user guide							

