

Premium Power Green

6-20kVA

Three-phase or Single-phase input
Single-phase output

Uninterruptible Power Supply

Main Features

- On-line double conversion
- Static and manual bypass
- Low impact on source
- Auto restart
- LCD screen
- Superior battery management
- 50 or 60Hz operation
- Wide input voltage range
- Programmable output
- Various battery options
- On-line or Standby operation
- RS-232 and contact interfaces
- SNMP communication options
- Free software



ECONOMY MODE
increases efficiency to 97%



Tel: +44 (0)1920 871077
Fax: +44 (0)1920 871337
Email: sales@cetronicpower.com


Your satisfaction is our motivation
www.cetronicpower.com

SPECIFICATIONS

MODEL	PG 6000	PG 8000	PG 10000	PG 10000ER	PG 15000	PG 20000	PG 20000ER
Rated Power (VA)	6000	8000	10000	10000	15000	20000	20000
Power (W)	5400	7200	9000	9000	13500	18000	18000
INPUT							
Nominal voltage	220-230-240 Vac	220-230-240 Vac 1ph / 380-400-415 Vac 3 ph + N					
Nominal frequency	50/60Hz ±10Hz						
BYPASS							
Voltage tolerance	160—276 Vac (selectable in Economy Mode or Smart Active Mode)						
Frequency tolerance	Selected frequency ±10Hz						
OUTPUT							
Nominal voltage	220-230-240 Vac selectable						
Voltage distortion	< 2% with linear load / < 5% with non-linear load						
Frequency	50/60Hz selectable or with automatic selection						
Static variation	± 1.5%						
Dynamic variation	≤ 5% in 20ms						
Waveform	Sinusoidal						
Crest factor	≥ 3:1						
BATTERIES							
Type	Sealed-lead acid						
Charging time	6-8 hours						
OVERLOAD TIMES							
100% < Load < 110%	5 min						
110% < Load < 130%	1 min						
130% < Load < 150%	10 sec						
OTHER FEATURES							
Weight (kg)	63	78	84		140	157	
Dimensions (HxWxD)	708 x 262 x 654mm					818 x 350 x 731mm	
Communication	USB / RS232 + slot for communications interface						
Regulations	EN 62040-1 EMC EN 62040-2 Directive 2006/95/EC - 2004/108 EC EN 62040-3						
Ambient temperature	0°C / + 40°C						
Relative humidity	< 95% non-condensing						
Colour	Dark grey RAL 7016						
Noise Level	< 40 dBA						

Optional Extras

- SNMP Network Interface Card
- Remote Alarm Panel
- External Manual Bypass Switch
- Extended Battery Back-Up Times
- Service and Maintenance Plans





Software Screenshot



Front panel display

PG 10-20



Issue 08/13



Tel: +44 (0)1920 871077
 Fax: +44 (0)1920 871337
 Email: sales@cetronicpower.com



Your satisfaction is our motivation
www.cetronicpower.com